



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Product Name Lead Acid Battery Filled with Acid  
Synonyms Lead Acid Battery, Wet, Filled with acid / Wet Cell Battery / Flooded battery

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Batteries for automotive  
Uses Advised Against None identified

#### 1.3 Details of the supplier of the safety data sheet

Supplier  
Company Identification Interstate Batteries Inc.  
Address 12770 Merit Drive Suite 1000  
Dallas, TX 75251  
Telephone: 866-884-4635

#### 1.4 Emergency telephone number

Emergency Phone No. 1-800-255-3924 (24 HOURS)  
Chemtel

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

US 29 CFR 1910.1200 Explosive, Category 1.3  
Acute toxicity (oral, inhalation, dermal), Category 4  
Skin corrosion/irritation, Category 1A  
Serious eye damage/irritation, Category 1  
Carcinogenicity, Category 1A  
Reproductive toxicity, Category 1A  
Lactation  
Specific target organ toxicity — repeated exposure, Category 2  
Hazardous to the Aquatic Environment – Chronic Hazard, Category 2

#### 2.2 Label elements

According to US 29 CFR 1910.1200

Product Name Lead Acid Battery Filled with Acid

Hazard Pictogram(s)





# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

Signal Word(s)

Danger

Hazard Statement(s)

Explosive; fire, blast or projection hazard.  
Harmful if swallowed, inhaled or in contact with skin.  
Causes severe skin burns and eye damage.  
May cause cancer.  
May damage fertility or the unborn child.  
May cause harm to breast-fed children.  
May cause damage to organs (Blood, Kidneys, Central nervous system) through prolonged or repeated exposure (Ingestion / Dermal).  
Toxic to aquatic life with long lasting effects.

Precautionary Statement(s)

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Avoid breathing fume/gas/mist/vapors.  
Avoid contact during pregnancy and while nursing.  
Wash hands and exposed skin thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Avoid release to the environment.  
Wear protective gloves/eye protection.  
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Call a POISON CENTER/doctor if you feel unwell.  
Take off contaminated clothing and wash it before reuse.  
Store locked up.  
Dispose of contents in accordance with local, state or national legislation.

### 2.3 Other hazards

Other hazards which do not result in classification

If overcharged or heated, it may erupt and cause a blast or projection hazard. May form explosive air/gas mixture during charging. Extremely flammable gas (hydrogen).

### 2.4 Unknown acute toxicity

Not applicable



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Not applicable.

#### 3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	%W/W	Component / element
Sulphuric acid	7664-93-9	30 - 38	Electrolyte
Lead	7439-92-1	48 - 59	Inorganic lead compounds
lead dioxide	1309-60-0	10.00	
lead sulphate	7446-14-2	< 1	
antimony	7440-36-0	0.5 - 4	
None hazardous polymer/ copolymer	Varies	5 - 10	Case Material

The specific chemical component identities and/or the exact component percentages of this material may be withheld as trade secrets.

This information is made available to health professionals, employees, and designated representatives in accordance with the applicable provisions of 29 CFR 1910.1200 (l)(1). Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, mutagen, and reproductive toxicant, respiratory tract and skin sensitizers in addition to oral/ inhalation acute toxicant in category 1 and 2). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents.

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures

Inhalation	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Keep patient at rest and give oxygen if breathing difficult. Apply artificial respiration if necessary (do not employ mouth-to-mouth method).
Skin Contact	Rinse skin immediately with plenty of water for 15-20 minutes. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Immediately call a POISON CENTER/doctor.
Eye Contact	Flush eyes with water for at least 15 minutes while holding eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
Ingestion	Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. Do not give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Not a likely route of exposure. If a battery ruptures:

Inhalation of mist or vapors may be harmful or fatal if inhaled in a confined area. May cause severe irritation and burns of the nose, throat and respiratory tract.

Direct eye contact with the liquid or exposure to vapors or mists may cause tearing, redness, swelling, corneal damage, and irreversible eye damage. Splashes in the eyes will cause severe burns.

Direct contact to skin and may result in redness, swelling, burns and severe skin damage. Skin contact may aggravate an existing dermatitis condition.

Accidental ingestion causes severe burns of the mouth or perforation of the esophagus or stomach. May be fatal if swallowed.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER/doctor. Treat symptomatically.



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1 Extinguishing Media

Suitable Extinguishing Media

As appropriate for surrounding fire. Foam; dry chemical. Do not use carbon dioxide directly on cells.

If a battery ruptures, use dry chemical, soda ash, lime, sand or carbon dioxide.

Unsuitable Extinguishing Media

None identified.

#### 5.2 Special hazards arising from the substance or mixture

May decompose in a fire, giving off toxic and irritant vapors. Lead, lead compounds and sulfuric acid fume may be released during a fire involving the product.

#### 5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Beware of acid splatter during water application and wear acid-resistant clothing, gloves, face and eye protection.

If batteries are on charge, shut off power to the charging equipment, but note that strings of series connected batteries may still pose risk of electric shock even when charging equipment is shut down. Dike fire control water for later disposal.

#### 5.4. Other information

Highly flammable hydrogen gas is generated during charging and operation of batteries. If ignited by burning cigarette, naked flame or spark may cause battery explosion with dispersion of casing fragments and corrosive liquid electrolyte.

Carefully follow manufacturer's instructions for installation and service.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

If a battery ruptures: Avoid contact with any spilled material. Avoid contact with skin and eyes. Do not breathe mist/vapors/spray. Provide adequate ventilation. Contain spill, isolate hazard area. Limit site access to emergency responders. Neutralize with sodium bicarbonate, soda ash, lime or other neutralizing agent. Ensure full personal protection (including respiratory protection) during removal of spillages. Place battery in suitable container for disposal. Dispose of contaminated material in accordance with applicable local, state and federal regulations. Sodium bicarbonate, soda ash, sand, lime or other neutralizing agent should be kept on-site for spill remediation.

#### 6.2 Environmental precautions

Lead and its compounds and sulfuric acid can pose a severe threat to the environment. Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body. Contamination of water, soil, and air should be prevented.

#### 6.3 Methods and material for containment and cleaning up

Neutralize with sodium bicarbonate, soda ash, lime or other neutralizing agent.

Ensure full personal protection (including respiratory protection) during removal of



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

spillages. Place battery in suitable container for disposal. Dispose of contaminated material in accordance with applicable local, state and federal regulations. Sodium bicarbonate, soda ash, sand, lime or other neutralizing agent should be kept on-site for spill remediation.

### 6.4 Reference to other sections

Acid resistant aprons, boots and protective clothing. ANSI approved safety glasses with side shields/face shield recommended. Ventilate enclosed areas. See Also Section 8, 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Handle batteries cautiously, do not tip to avoid spills. Avoid contact with internal components. Make certain vent caps are on securely. Unless involved in recycling operations, do not breach the casing or empty the contents of the battery. Wear protective clothing when filling or handling batteries. Follow manufacturer's instructions for installation and service. Do not allow conductive material to touch the battery terminals. Short circuit may occur and cause battery failure and fire. There may be increasing risk of electric shock from strings of connected batteries. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Eyewash stations and safety showers should be provided with unlimited water supply. Handle in accordance with good industrial hygiene and safety practice. Charge batteries in areas with adequate ventilation.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact during pregnancy and while nursing. Do not eat, drink or smoke when using this product.

### 7.2 Conditions for safe storage, including any incompatibilities

Store batteries under roof in cool, dry, well-ventilated areas separated from incompatible materials and from activities that may create flames, spark, or heat. Store on smooth, impervious surfaces provided with measures for liquid containment in the event of electrolyte spills. Keep away all sources of gas ignition and do not allow metallic articles to simultaneously contact the negative and positive terminals of a battery. Follow manufacturer's instructions for installation and service. Keep away from combustible materials, organic chemicals, reducing substances, metals, strong oxidizers and water. Use banding or stretch wrap to secure items for shipping.

Storage temperature	Ambient. Do not use or store near heat or open flame.
Storage life	Stable under normal conditions.
Incompatible materials	None known.

### 7.3 Specific end use(s)

Not known.

**Charging:** There is a possible risk of electric shock from charging equipment and from strings of series connected batteries, whether or not being charged. Shut-off power to chargers whenever not in use and before detachment of any circuit connections. Batteries being charged will generate and release flammable hydrogen gas. Charging space should be ventilated. Keep battery vent caps in position. Prohibit smoking and avoid creation of flames and sparks nearby. Wear face and eye protection when near batteries being charged.



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

##### 8.1.1 Occupational Exposure Limits

Occupational Exposure Limits						
SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m <sup>3</sup> )	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note:
Sulfuric acid	7664-93-9		0.2			ACGIH TLV, T, A2, M
Sulfuric acid	7664-93-9		1			NIOSH REL Z-1
Sulfuric acid	7664-93-9		0.1		3	OSHA PEL
Sulfuric acid	7664-93-9		1			OSHA PEL Z-1
Antimony and compounds, as Sb	7440-36-0		0.5			ACGIH TLV
Antimony and compounds (as Sb)	7440-36-0		0.5			NIOSH REL Z-1
Antimony and compounds, as Sb	7440-36-0		0.5			OSHA PEL
Antimony and compounds (as Sb)	7440-36-0		0.5			OSHA PEL Z-1
Lead and inorganic compounds, as Pb	7439-92-1		0.05			ACGIH TLV, A3
Lead, inorganic (as Pb)	7439-92-1		0.05			NIOSH REL Z-1
Lead (metallic) and inorganic compounds, dust and fume, as Pb	7439-92-1		0.05			OSHA PEL
Lead and inorganic compounds, as Pb	1309-60-0		0.05			ACGIH TLV, A3
Lead, inorganic (as Pb)	1309-60-0		0.05			NIOSH REL Z-1
Lead (metallic) and inorganic compounds, dust and fume, as Pb	1309-60-0		0.05			OSHA PEL
Lead and inorganic compounds, as Pb	7446-14-2		0.05			ACGIH TLV, A3
Lead, inorganic (as Pb)	7446-14-2		0.05			NIOSH REL Z-1
Lead (metallic) and inorganic compounds, dust and fume, as Pb	7446-14-2		0.05			OSHA PEL

Remark  
ACGIH TLV

Notes  
The American Conference of Governmental Industrial Hygienists (ACGIH®) Threshold Limit Values (TLVs®) 2020



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

T	Thoracic particulate matter
A2	Suspected Human Carcinogen
M	Classification refers to sulfuric acid contained in strong inorganic acid mists.
NIOSH REL Z-1	National Institute for Occupational Safety and Health (NIOSH) Recommended Exposure Limits (RELs) from the NIOSH Pocket Guide to Chemical Hazards table Z-1: Up to 10-hour time weighted average (TWA) during a 40-hour work week
OSHA PEL	Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
OSHA PEL Z-1	Occupational Safety and Health Administration (OSHA) Permissible Exposure Limit (PEL) from 29 CFR 1910.1000 Z-1 Table
A3	Confirmed Animal Carcinogen with Unknown Relevance to Humans

BEI: Biological Exposure Indices (ACGIH)						
Substances	CAS Number	Sampling	Tissues	Control parameters	Biological monitoring guidance value	Comments
Lead and inorganic compounds	7439-92-1	Not critical	blood	Lead	200 µg/L	p
Lead and inorganic compounds	1309-60-0	Not critical	blood	Lead	200 µg/L	p
Lead and inorganic compounds	7446-14-2	Not critical	blood	Lead	200 µg/L	p

Remark	Notes
p	Persons applying this BEI® are encouraged to counsel female workers of child-bearing age about the risk of delivering a child with a PbB over the current CDC reference value.(CDC: Guidelines for the identification and management of lead exposure in pregnant and lactating women, 2010.)

### 8.2 Exposure controls

8.2.1. Appropriate engineering controls Store and handle in well-ventilated area. Use with ventilation, local exhaust ventilation or breathing protection. If mechanical ventilation is used, components must be acid-resistant.

In areas where water and sulfuric acid solutions are handled in concentrations greater than 1%, emergency eyewash stations and showers should be provided, with unlimited water supply.

#### 8.2.2. Personal protection equipment



Eye Protection NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT. If necessary to handle damaged product where exposure to the organic electrolyte is a possibility, chemical splash goggles and a face shield are recommended.



Skin protection NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT. If battery case is damaged, use rubber or plastic acid-resistant gloves with elbow-length gauntlet, acid-resistant apron, clothing and boots.



Respiratory protection NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT. When concentrations of sulfuric acid mist are known to exceed PEL, use NIOSH or MSHA-approved respiratory protection.



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021



Thermal hazards

None known.

8.2.3. Environmental Exposure Controls Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

### 8.3 Other information

Chemically impervious apron and face shield recommended when adding water or electrolyte to batteries. Wash Hands after handling.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	Manufactured Article. Contains Liquid. Color : Clear (Electrolyte)
Odor	Sharp, penetrating, pungent odor
Odor Threshold	Not known.
pH	< 1 - 2
Melting Point/Freezing Point	ca 320F Polypropylene
Initial boiling point and boiling range	203 - 250 F Electrolyte
Flash Point	Not known.
Evaporation Rate	< 1 Relative Evaporation Rate (Butyl Acetate = 1)
Flammability (solid, gas)	Not known.
Upper/lower flammability or explosive limits	Flammable Limit Lower - 4.1% (Hydrogen) Flammable Limit Upper - 74.2 % (Hydrogen)
Vapor pressure	10 – 10.95 Vapour Pressure (mm Hg)
Vapor density	> 1 Vapour Density (Air=1)
Density (g/ml)	Not known.
Relative density	1.215 - 1.350 Density (water=1)
Solubility(ies)	Solubility (Water) : 100% Soluble Electrolyte Solubility (Other) : Not known.
Partition coefficient: n-octanol/water	Not known.
Auto-ignition temperature	1076F (Hydrogen)
Decomposition Temperature (°C)	Not known.
Viscosity	Not known.
Explosive properties	Not known.
Oxidizing properties	Not known.

### 9.2 Other information

None.





# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity

None anticipated.

#### 10.2 Chemical Stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

#### 10.4 Conditions to avoid

Prolonged overcharge at high current. Keep away from heat and sources of ignition.  
Mechanical impact.

#### 10.5 Incompatible materials

This article is considered stable under normal conditions. If a battery ruptures:  
Reacts with organic materials. Strong reducing agents and metals.  
Electrolyte: Contact with combustibles and organic materials may cause fire and explosion. Also reacts violently with strong reducing agents, metals, sulfur trioxide gas, strong oxidizers, and water. Contact with metals may produce toxic sulfur dioxide fumes and may release flammable hydrogen gas.

#### 10.6 Hazardous decomposition products

Electrolyte: Sulfur trioxide, carbon monoxide, sulfuric acid mist, sulfur dioxide, hydrogen sulfide.  
Lead compounds: Temperatures above the melting point are likely to produce toxic metal fume, vapor, or dust; contact with strong acid or base or presence of nascent hydrogen may generate highly toxic arsine gas.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

##### Acute toxicity - Ingestion

Self classification: Harmful if swallowed.

Ingesting Sulfuric Acid may cause severe irritation of mouth, throat, esophagus and stomach.

Acute ingestion of Lead Compounds may cause abdominal pain, nausea, vomiting, diarrhea and severe cramping. This may lead rapidly to systemic toxicity and must be treated by a physician.

##### Acute toxicity - Skin Contact

Self classification: Harmful in contact with skin.

Inhalation of sulfuric acid vapors or mists may cause severe respiratory irritation.  
Inhalation of lead dust or fumes may cause irritation of upper respiratory tract and lungs.

##### Acute toxicity - Inhalation

Self classification: Harmful if inhaled.

Contact with Arsenic compounds may cause dermatitis and skin hyperpigmentation.



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021      Revision date: n/a      Printed: 03/19/2021

Skin corrosion/irritation

Calculation method : Causes severe skin burns and eye damage.  
Skin contact with Sulfuric Acid causes severe irritation, burns, and ulceration.

Serious eye damage/irritation

Calculation method : Causes serious eye damage.

Skin sensitization data

Not classified.

Respiratory sensitization data

Not classified.

Germ cell mutagenicity

Not classified.

Carcinogenicity

Self classification: May cause cancer.

Sulfuric Acid	
IARC	Group 1 - Carcinogen

Lead compounds	
IARC	Group 2A - Likely Carcinogenic to animal at extream doses

Arsenic compounds	
IARC	Group 1 - Carcinogen

Reproductive toxicity

Self classification: May damage fertility or the unborn child.

Lactation

May cause harm to breast-fed children.

STOT - single exposure

Not classified.

STOT - repeated exposure

Self classification: Causes damage to organs (Blood Kidneys Central nervous system) through prolonged or repeated exposure (Ingestion / Dermal).

Aspiration hazard

Not classified.

### 11.2 Other information

All heavy metals, including the hazardous ingredients in this product, are taken into the body primarily by inhalation and ingestion. Most inhalation problems can be avoided by adequate precautions such as ventilation and respiratory protection covered in Section 8. Follow good personal hygiene to avoid inhalation and ingestion: wash hands, face, neck and arms thoroughly before eating, smoking or leaving the work site. Keep contaminated clothing out of non- contaminated areas, or wear cover clothing when in such areas. Restrict the use and presence of food, tobacco and cosmetics to non-contaminated areas. Work clothes and work equipment used in contaminated areas must remain in designated areas and never taken home or laundered with personal non-contaminated clothing. This product is intended for industrial use only and should be isolated from children and their environment.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Toxicity - Aquatic invertebrates

Not known.

Toxicity - Fish

Not known.



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

Toxicity - Algae	Not known.
Toxicity - Sediment Compartment	Not classified.
Toxicity - Terrestrial Compartment	Not classified.
<b>12.2 Persistence and degradability</b>	
	Not known.
<b>12.3 Bioaccumulative potential</b>	
	Not known.
<b>12.4 Mobility in soil</b>	
	Not known.
<b>12.5 Other adverse effects</b>	
	Not known.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Spent Batteries: Send to secondary lead smelter for recycling. Spent lead-acid batteries are not regulated as hazardous waste when the requirements of 40 CFR Section 266.80 are met. Spilled sulfuric acid is a characteristic hazardous waste; EPA hazardous waste number D002 (corrosivity) and D008 (lead).

Electrolyte: Place neutralized slurry into sealed acid resistant containers and dispose of as hazardous waste, as applicable. Large water diluted spills, after neutralization and testing, should be managed in accordance with approved local, state, and federal requirements. Consult state environmental agency and/or federal EPA.

#### 13.2 Additional Information

Disposal should be in accordance with local, state or national legislation. Following local, State/Provincial, and Federal/National regulations applicable to end-of-life characteristics will be the responsibility of the end-user.

### SECTION 14: TRANSPORT INFORMATION

#### In accordance with DOT

49 CFR 173.159

#### 14.1 UN number

UN No. 2794

#### 14.2 UN proper shipping name

UN proper shipping name Batteries, wet, filled with acid

#### 14.3 Transport hazard class(es)

DOT Class 8

DOT Label Corrosive

Packaging group III



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

49 CFR 173.159(e) Specifies that when transported by highway or rail, electric storage batteries containing electrolyte or corrosive battery fluid are not subject to any other requirements of this subchapter, if all of the following are met:

- (1) No other hazardous materials may be transported in the same vehicle;
- (2) The batteries must be loaded or braced so as to prevent damage and short circuits in transit;
- (3) Any other material loaded in the same vehicle must be blocked, braced, or otherwise secured to prevent contact with or damage to the batteries; and
- (4) The transport vehicle may not carry material shipped by any person other than the shipper of the batteries.

If any of the above-referenced requirements are not met, the batteries must be shipped as fully-regulated Class 8 Corrosive hazardous materials.

### Transport by sea (IMDG)

IMDG Proper shipping name:	Batteries, wet, filled with acid
Hazards label	Corrosive
IMDG Class	8
Packaging group	n/a
UN identification	UN2794

### Air transport (IATA/ICAO)

IATA Proper Shipping Name	BATTERIES, WET, FILLED WITH ACID,
Hazards label	Corrosive
IMDG Class	8
Packaging group	n/a
UN identification	UN2794

## SECTION 15: REGULATORY INFORMATION

### 15.1 US Federal Regulations

Toxic and hazardous substances (29 CFR 1910; Subpart Z)	Listed : 7664-93-9, 7440-36-0, 7439-92-1, 1309-60-0, 7446-14-2
National emission standards for hazardous air pollutants (40 CFR 61.01)	Not listed
SARA Title III Section 313	Not listed
TSCA (Toxic Substance Control Act)	Listed : 7664-93-9 (Active), 7440-36-0 (Active), 7439-92-1 (Active), 9003-07-0 (Active), 1309-60-0 (Active), 7446-14-2 (Active)
CAA 602 - Ozone Depleting Substances (ODS)	Not listed

### 15.2 US State Regulations

State Right to Know Lists



**WARNING:** Battery posts, terminals, and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm, and during charging, strong inorganic acid mists containing sulfuric



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

acid are evolved, a chemical Known to the State of California to cause cancer. Wash hands after handling.

[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Proposition 65 (California)

Minnesota

New Jersey

Pennsylvania

Rhode Island

### 15.3 Other

OSPAR List of Chemicals for Priority Action

OSHA (List of Highly Hazardous Chemicals, Toxics and Reactives)

NTP (National Toxicology Program )

IARC (International Agency for Research on Cancer )

Listed : 7439-92-1

Listed : 7664-93-9, 7440-36-0, 7439-92-1, 1309-60-0, 7446-14-2

Listed : 7664-93-9, 7440-36-0, 7439-92-1, 1309-60-0, 7446-14-2

Listed : 7664-93-9, 7440-36-0, 7439-92-1, 1309-60-0, 7446-14-2

Listed : 7664-93-9, 7439-92-1

Listed : 7439-92-1


Not listed

Listed : 7664-93-9, 7439-92-1, 1309-60-0, 7446-14-2

Listed : 7664-93-9, 7439-92-1, 9003-07-0, 1309-60-0, 7446-14-2

## SECTION 16: OTHER INFORMATION

### NFPA rating



### NFPA Hazards scale

0= Minimal

1= Slight

3= Moderate

4= Serious

5= Severe

## LEGEND

### Acronyms

ATE: Acute Toxicity Estimate

CAS : Chemical Abstracts Service

IATA : International Air Transport Association

ICAO : International Civil Aviation Organization

IMDG : International Maritime Dangerous Goods

LTEL : Long term exposure limit



# Lead Acid Battery Filled with Acid

## Safety Data Sheet

According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 02/01/2021

Revision date: n/a

Printed: 03/19/2021

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

UN : United Nations

Key literature references and sources for US CFR 1910.1200

data used to compile the SDS

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.